

MASCHIO**GASPARDO****SINCE 1964**

Growing Together

VIRAT RANGE**ROTARY TILLERS****IMPLEMENT
OF THE YEAR**

ITOTY 2019

**ROTAVATOR
OF THE YEAR**ITOTY 2019
& 2021NOW COME WITH
**2 YEARS
WARRANTY*****1+1**EXTENDED
WARRANTY**EASY****FINANCE**

AVAILABLE*

VIRAT LIGHT**VIRAT PLUS****VIRAT PRO****VIRAT REGULAR****VIRAT HC****VIRAT J**

Low Maintenance



Less Diesel Consumption



Best Soil Pulverization

Multi Speed
Powerful GearboxDuo-cone
Water Proof SealingHigh Quality
Italian Boron Steel Blades

Less Load on Tractor

High Quality
Nano Coated Paint

V092021-ENGLISH

* TERMS & CONDITIONS APPLY.

VIRAT LIGHT

Model	HP Range	Working Width (cm)	Total Width (cm)	*Working Depth		No. of Blades	**Weight (kg)
				(cm)	(inches)		
V-LIGHT 125	30-35	135	155	22	8.5	30	345
V-LIGHT 125	30-35	125	145	22	8.5	36	361
V-LIGHT 145	35-40	145	165	22	8.5	42	370
V-LIGHT 150	35-40	150	170	22	8.5	42	377
V-LIGHT 165	40-45	165	185	22	8.5	36	393
V-LIGHT 165	40-45	165	185	22	8.5	48	398
V-LIGHT 185	45-50	185	205	22	8.5	42	417
V-LIGHT 185	45-50	185	205	22	8.5	54	425
V-LIGHT 205	50-60	205	225	22	8.5	48	433
V-LIGHT 205	50-60	205	225	22	8.5	60	447

*It may vary according to soil condition and soil type.
**Machine weight is excluding Cardan shaft and Tool kit.

ADVANTAGES

- Light in weight
- Oil bath lubricated rotor bearings
- Water-proof duo cone oil seals
- Optional : Single speed gearbox



GEARBOX

540 rpm	1000 rpm	rpm
Multi Speed		
20-16	NA	269
19-17	NA	241
17-19	NA	193
16-20	NA	172
NA	15-21	285

TRANSMISSION TYPE

BEST IN SOFT & SANDY SOIL



COULTER DISC AVAILABLE IN ALL VIRAT MODELS *

VIRAT PRO

Model	HP Range	Working Width (cm)	Total Width (cm)	*Working Depth		No. of Blades	**Weight (kg)
				(cm)	(inches)		
V-PRO 125	35-45	125	145	22	8.5	30	365
V-PRO 145	40-50	145	165	22	8.5	36	386
V-PRO 150	40-50	150	170	22	8.5	36	400
V-PRO 165	50-55	165	185	22	8.5	42	428
V-PRO 170	50-55	165	185	22	8.5	36	421
V-PRO 185	55-60	185	205	22	8.5	42	445
V-PRO 205	60-65	205	225	22	8.5	48	475
V-PRO 205***	60-70	205	225	22	8.5	48	503
V-PRO 230	60-75	230	250	22	8.5	54	495
V-PRO 230***	70-80	230	250	22	8.5	54	530
V-PRO 250***	75-90	250	270	22	8.5	60	651
V-PRO 275***	80-95	275	295	22	8.5	66	687
V-PRO 305***	90-110	305	325	22	8.5	72	718

*It may vary according to soil condition and soil type.
**Machine weight is excluding cardan shaft and tool kit.
*** Machines fitted with GGB gearbox

ADVANTAGES

- Multi-speed gear box (4 speeds)
- Reduced maintenance
- Depth skids with multiple adjustment
- Center and offset version available
- Optional : Single speed gearbox



GEARBOX

540 rpm	1000 rpm	rpm
Multi Speed		
18-15	NA	257
15-18	NA	178
17-16	NA	227
16-17	NA	201
NA	13-20	257

TRANSMISSION TYPE

GEARBOX (for GGB model)

540 rpm	1000 rpm	rpm
Multi Speed		
19-16	NA	267
16-19	NA	189
18-19	NA	238
17-18	NA	212
NA	13-22	246

TRANSMISSION TYPE

BEST IN BLACK & HARD SOIL



VIRAT PLUS

Model	HP Range	Working Width (cm)	Total Width (cm)	*Working Depth		No. of Blades	**Weight (kg)
				(cm)	(inches)		
V-PLUS 125	30-35	125	145	22	8.5	36	365
V-PLUS145	35-45	145	165	22	8.5	42	388
V-PLUS 165	40-50	165	185	22	8.5	48	415
V-PLUS 185	45-55	185	205	22	8.5	54	451
V-PLUS 205	50-60	205	225	22	8.5	60	484
V-PLUS 205***	55-65	205	225	22	8.5	60	510

*It may vary according to soil condition and soil type.
**Machine weight is excluding cardan shaft and tool kit.
*** Machines fitted with GGB gearbox

ADVANTAGES

- Rear bonnet adjustment with double spring
- Oil bath lubricated rotor bearings
- Water-proof duo cone oil seals
- Optional : Single speed gearbox



GEARBOX

540 rpm	1000 rpm	rpm
Multi Speed		
20-16	NA	258
19-17	NA	230
17-19	NA	185
16-20	NA	166
NA	15-21	273

TRANSMISSION TYPE

GEARBOX (for GGB model)

540 rpm	1000 rpm	rpm
Multi Speed		
19-16	NA	267
16-19	NA	189
18-19	NA	238
17-18	NA	212
NA	13-22	246

TRANSMISSION TYPE

BEST IN SOFT & SANDY SOIL



VIRAT REGULAR

Model	HP Range	Working Width (cm)	Total Width (cm)	*Working Depth		No. of Blades	**Weight (kg)
				(cm)	(inch)		
V-SP 125	30-35	125	145	22	8.5	30	355
V-SP 145	35-45	145	165	22	8.5	36	378
V-SP 165	40-50	165	185	22	8.5	42	420
V-SP 185	45-55	185	205	22	8.5	48	445
V-SP 205	50-60	205	225	22	8.5	54	477
V-SP 205***	55-65	205	225	22	8.5	54	500
V-SP 230	60-75	230	250	22	8.5	60	505
V-SP 230***	65-80	230	250	22	8.5	60	535
V-SP 275***	75-95	275	295	22	8.5	72	685
V-SP 305***	80-110	305	325	22	8.5	78	715

*It may vary according to soil condition and soil type.
**Machine weight is excluding cardan shaft and tool kit.
*** Machines fitted with GGB gearbox

ADVANTAGES

- Gear drive transmission
- Models available in single speed gearbox
- Transmission spacer tubes connected to the frame through 4 heavy duty cast steel supports to increase rigidity of structure and resistance to vibration



GEARBOX

540 rpm	1000 rpm	rpm
Multi Speed		
20-16	NA	258
19-17	NA	230
17-19	NA	185
16-20	NA	166
NA	15-21	273

TRANSMISSION TYPE

GEARBOX (For 230 model)

540 rpm	1000 rpm	rpm
Multi Speed		
18-15	NA	257
15-18	NA	178
17-16	NA	227
16-17	NA	201
NA	13-20	257

TRANSMISSION TYPE

GEARBOX (for GGB model)

540 rpm	1000 rpm	rpm
Multi Speed		
19-16	NA	267
16-19	NA	189
18-19	NA	238
17-18	NA	212
NA	13-22	246

TRANSMISSION TYPE

BEST IN STICKY SOIL



VIRAT HC



Model	HP Range	Working Width (cm)	Total Width (cm)	*Working Depth		No. of Blades	**Weight (kg)
				(cm)	(inches)		
V-HC 125	35-40	125	145	22	8.5	30	380
V-HC 150	40-50	150	170	22	8.5	36	410
V-HC 165	50-55	165	185	22	8.5	36	432
V-HC 185	55-65	185	205	22	8.5	42	462
V-HC 205	60-65	205	225	22	8.5	48	485
V-HC 205***	60-70	205	225	22	8.5	48	515
V-HC 230***	70-80	230	250	22	8.5	54	542

*It may vary according to soil condition and soil type.

**machine weight is excluding cardan shaft and tool kit.

*** Machines fitted with GGB gearbox

GEARBOX

540 rpm	1000 rpm	rpm
Multi Speed		
18-15	NA	257
15-18	NA	178
17-16	NA	227
16-17	NA	201
NA	13-20	257
TRANSMISSION TYPE		

GEARBOX (For GGB model)

540 rpm	1000 rpm	rpm
Multi Speed		
19-16	NA	267
16-19	NA	189
18-17	NA	238
17-18	NA	212
NA	13-22	246
TRANSMISSION TYPE		

ADVANTAGES

- Durable and reliable side transmission drive
- Best quality, long lasting Italian boron steel blades
- Dome shape bonnet for better pulverization
- Depth skids with multiple adjustment
- Optional : Single speed gearbox

BEST IN HARD & STICKY SOIL



VIRAT J

Model	HP Range	Working Width (cm)	Total Width (cm)	*Working Depth		No. of Blades	**Weight (kg)
				(cm)	(inch)		
VIRAT-J 145	35-40	145	165	22	8.5	60	374
VIRAT-J 165	45-50	165	185	22	8.5	66	403
VIRAT-J 175	45-55	175	195	22	8.5	66	414
VIRAT-J 185	50-55	185	205	22	8.5	72	421
VIRAT-J 205	55-60	205	225	22	8.5	78	440

*It may vary according to soil condition and soil type.

**Machine weight is excluding cardan shaft and Tool kit.

ADVANTAGES

- Rear bonnet adjustment with double spring
- High mixing level of crop residues
- Multi-speed gear box (4 speeds)
- Reduced maintenance
- Depth skids with multiple adjustment



GEARBOX

540 rpm	1000 rpm	rpm
Multi Speed		
20-16	NA	258
19-17	NA	230
17-19	NA	185
16-20	NA	166
NA	15-21	273
TRANSMISSION TYPE		

BEST IN SOFT SOIL



MASCHIO GASPARDI INDIA PVT LTD
Plant : Plot No F 27 MIDC, Village Karegaon,
Tal Shirur 412220 Ranjangaon, District - Pune, India
Tel. +91 02138 612500 | Email. info@maschio.in

MASCHIO GASPARDI INDIA PVT LTD
CORPORATE OFFICE : Off. No. 203-204, Tower-II,
World Trade Center, Kharadi, Pune 411014, India.
Tel. +91 02138 612500 | Email. info@maschio.in

Note: Maschio Group reserves the right at any time to make changes to the design or specifications shown or described, to add or remove features, without any notice or obligations on Purchased before or after such changes are made.

AUTHORIZED DEALER :